

 <b>2024 (MYR) Cayenne Models</b> Technical Data <b>MSRP</b>		Cayenne	Cayenne E-Hybrid	Cayenne S	Cayenne Coupe	Cayenne E-Hybrid Coupe	Cayenne S Coupe	Cayenne Turbo GT		
		\$79,200	\$91,700	\$95,700	\$84,300	\$95,700	\$102,100	\$196,300		
<b>Engine</b>										
Engine layout	Front Engine		Front Engine	Front Engine	Front Engine	Front Engine	Front Engine	Front Engine		
Engine type	Turbocharged V6 90°		Turbocharged V6 90°	Twin-Turbo V8 90°	Turbocharged V6 90°	Turbocharged V6 90°	Twin-Turbo V8 90°	Twin-Turbo V8 90°		
Displacement	2995		2995	3996	2995	2995	3996	3996		
Maximum power output @ engine speed	348 @ 5,400 - 6,400		300 @ 5,400 - 6,400	468 hp @ 6,000	348 @ 5,400 - 6,400	300 @ 5,400 - 6,400	468 hp @ 6,000	650 hp @ 6,000		
Maximum torque @ engine speed	368 lb.-ft. @ 1,500		309 lb.-ft. @ 1,400 - 4,800	442 lb.-ft. @ 2,000	368 lb.-ft. @ 1,500	309 lb.-ft. @ 1,400	442 lb.-ft. @ 2,000	626 lb.-ft. @ 2,300		
Electric Motor max power @ rpm			174 @ 3,200			174 @ 3,200				
Electric Motor max torque @ rpm			339 lb. -ft. @ 2,690			339 lb. -ft. @ 3,200				
Battery Size (Gross/Net) kWh			25.9/21.8			25.9/21.8				
Combined power			463 hp			463 hp				
Combined torque			479 lb-ft			479 lb-ft				
Maximum engine speed	6,500		6,500	6,800	6,500	6,500	6,800	6,800		
Compression ratio	11.2:1		11.2:1	9.7:1	11.2:1	11.2:1	9.7:1	9.7:1		
Weight to Power ratio (lbs/hp)	13.4		11.6	10.4	13.6	11.7	10.6	7.8		
<b>Chassis &amp; suspension</b>										
Front Axle	Multi-Link Front Axle with Electromechanical Steering									
Rear Axle	Multi-Link Axle with Subframe and Dissolved Spring Damper Arrangement									
Steering System	Electromechanical Steering									
<b>Brakes and Wheels</b>										
Caliper type	Aluminum Monobloc Fixed Calipers front and rear									
Number of pistons (front/rear)	6	4	6	4	6	4	6	4	10	4
Caliper color	Black		Black		Red		Black		Black	
Rotor Design/material	Internally vented/Cast		Internally vented/Cast		Internally vented/Cast		Internally vented/Cast		Internally vented and Cross	
Rotor diameter (front rear) mm	390	358	410	358	410	358	390	358	410	410
Rotor thickness (front rear) mm	38	28	38	28	38	28	38	28	38	32
Name and option #	20" Cayenne Design wheels (43E)		20" AeroDesign wheels (57N)		20" Cayenne S wheels (57P)		20" Cayenne Design wheels (43E)		20" AeroDesign wheels (57N)	
Wheels	9.0J x 20 et 50 10.5J x 20 et 64		9.0J x 20 et 50 10.5J x 20 et 64		9.0J x 20 et 50 10.5J x 20 et 64		9.0J x 20 et 50 10.5J x 20 et 64		9.0J x 20 et 50 10.5J x 20 et 64	
Tires	255/55 R 20 295/45 R 20		255/55 R 20 295/45 R 20		255/55 R 20 295/45 R 20		255/55 R 20 295/45 R 20		255/55 R 20 295/45 R 20	
<b>Transmission</b>										
Drive	All-wheel Drive		All-wheel Drive	All-wheel Drive	All-wheel Drive	All-wheel Drive	All-wheel Drive	All-wheel Drive		
Number of gears	8		8	8	8	8	8	8		
Transmission type	Tiptronic S, automatic		Tiptronic S, automatic	Tiptronic S, automatic	Tiptronic S, automatic	Tiptronic S, automatic	Tiptronic S, automatic	Tiptronic S, automatic		
<b>Dimensions, Aerodynamics &amp; Weight</b>										
Length	194.1		194.1	194.1	194.1	194.1	194.1	194.2		
Wheelbase	114		114	114	114	114	114	114		
Width (mirrors folded/open)	78.6/86.4		78.6/86.4	78.6/86.4	78.6/86.4	78.6/86.4	78.6/86.4	78.6/86.4		
Height	66.9		66.8	66.8	66.1	65.9	66.1	64.9		
Track width front	1676		1676	1676	1676	1676	1676	1691		
Track width rear	1653		1653	1653	1653	1671	1653	1684		
Drag coefficient (Cd)	0.36		0.36	0.35	0.36	0.35	0.36	0.37		
Cargo Area Volume (cubic feet)	26.91		25.77	26.91	24.32	22.77	24.32	23.78		
Cargo Area Volume (cubic feet) seats folded	60.31		55.19	60.31	53.04	47.46	53.04	52.47		
Fuel Tank Capacity - refill volume (gal)	23.7		19.8	23.7	23.7	19.8	23.7	23.7		
Curb weight (lbs)	4678		5348	4874	4740	5415	4941	5055		
Max payload (lbs)	1572		1541	1585	1477	1442	1475	853		
Max trailer load (braked/unbraked)	7716/1653		7716/1653	7716/1653	7716/1653	7716/1653	7716/1653	N/A		
<b>Suspension</b>										
Suspension Type (2 Valve / 2 Chamber)	Steel Spring w/PASM (2V)		Steel Spring w/PASM (2V)	Steel Spring w/PASM (2V)	Steel Spring w/PASM (2V)	Steel Spring w/PASM (2V)	Steel Spring w/PASM (2V)	Air Suspension (2C) w/PASM (2V)		
Ground Clearance (std/normal level)	8.3"		8.1"	8.2"	8.4"	8.0"	8.3"	6.8"		
Max Wading Depth (std/normal level)	19.6"		11.0"	19.6"	19.6"	11.0"	19.6"	18.1"		
Approach Angle (std/normal level)	25.4°		25.6°	25.3°	25.5°	25.7°	25.3°	17.6°		
Breakover Angle (std/normal level)	18.9°		18.7°	18.8°	19.0°	18.5°	18.9°	16.3°		
Departure Angle (std/normal level)	22.3°		21.9°	22.1°	22.5°	21.7°	22.3°	18.8°		
<b>Performance</b>										
Top Track Speed (mph)	154		158	169	154	158	169	189		
Acceleration 0 – 60/with Sport Plus (secs)	5.7/5.4		/4.6	4.7/4.4	/5.4	/4.6	/4.4	/3.1		
1/4 mile from standing start (secs)	14.3/14.1		/13.2	13.2/13.1	/14.1	/13.2	/13.1	/11.6		